

Heavy duty elastic bands

These pallet bands are designed to withstand high forces. Thanks to its braided textile outer covering the FT60 range has a superior UV resistance and a high resistance to shear.

Cautions for use and storage:

- Use within a temperature range of 0 to +20°C
- Avoid prolonged exposure to sunlight or other sources of ultra-violet light
- Do not allow contact with petroleum products

Storage life: Stored in the carton of origin, in accordance with the conditions recommended above a shelf life in excess of 4 years can be expected.

Certified that the product and the packing contain no heavy metals or lead.

Article	FT6011140RE	FT6016150BL	FT6022150GI
Colour	Red	Blue	Grey
Circumference in mm	2800	3000	3000
Width of tape in mm	11	16	22
Thickness in mm		3	
Net weight for 100 m in Kg	2.4		4.7
Strength at 25% stretch in Newton	30	37	58
Strength at 50% stretch in Newton	40	52	81
Strength at 75% stretch in Newton	52	69	108
Strength at 100% stretch in Newton	69	97	147
Elongation at break in %		250	
Force at break in Newton	610	1050	1421
Tolerance on stretch and break		+/- 15%	
Recommended range use		20% < X < 50%	
Packing per carton	200 pieces	100 pieces	100 pieces

HIGH DENIER UV resistant INDUSTRIAL Polypropylene YARN

Outer Covering

	Unit	Value
Denier	D	915
Linear density	dtex	1015
Tolerance of linear density	+/-%	2.5
Break tenacity	Cn/dtex	3.4
Breaking strength	N	34
Breaking elongation	%	33
Elongation CV	+/-	2.8
Oil content	%	2.0

Rubber Core

Multifilament of natural extruded rubber with anti-U.V. agents